

EAN: 6414150083457

[www.oras.com/en/products/oras/product/1015F](http://www.oras.com/en/products/oras/product/1015F)

Washbasin faucet. Swivel spout (125 mm) and aerator. Spout's swing angle is factory preset at 120° (can be limited to 40°-80°). There are also in-built limitation options for water temperature and maximum flow-rate.

F=with flexible pipes.



- Bathroom
- Single-lever
- Deck mounted
- Chrome
- Swivel spout
- Single operating lever/handle, Hot/Cold symbols
- Limitation option for maximum temperature and flow-rate
- $\varnothing$  40 mm ceramic cartridge for flow and temperature control
- Flexible inlet pipes
- 3S-installation system for safe and simple mounting

## Technical data

### Flow properties

Flow-rate at 300 kPa	<b>0.18 l/s</b>
Pressure loss with flow (0.1 l/s)	<b>95 kPa</b>

### Technical properties

Hot water supply	<b>max. +80°C</b>
Working pressure	<b>50 - 1000 kPa</b>
Connection size	<b>G3/8</b>
Projection	<b>133 mm</b>
Material	<b>Brass</b>

### Regulations

EN standard	<b>EN 817</b>
Noise class	<b>I (ISO 3822) Oras lab.</b>



