

Liitin UNI-Grip L PN16

Rakenne :

- Runko, pultit ja insertit (lisävaruste): Haponkestävä teräs W5 (1.4571)

Lämpötila/Paine:


- Käyttölämpötila EPDM: -30°C - 125°C
- Käyttölämpötila NBR: -20°C - 80°C

Vaihtoehto:

- Viton-tyyppiset tiivisteet tilauksesta

Ulkohalk. nimell. (mm)	EPDM Koodi	LVI	Paino (kg)	NBR Koodi	LVI
21,3 - 21,6	779 724 001	013 45 00	0,2	779 721 001	
26,9 - 28,0	779 724 002	013 45 01	0,2	779 721 002	
30,0	779 724 003	013 45 02	0,2	779 721 003	
33,7 - 35,0	779 724 004	013 45 03	0,2	779 721 004	
38,0	779 724 005	013 45 04	0,4	779 721 005	
42,4	779 724 006	013 45 05	0,4	779 721 006	
44,5	779 724 007	013 45 06	0,4	779 721 007	
48,3	779 724 008	013 45 07	0,4	779 721 008	013 46 02
54,0 - 57,0	779 724 009	013 45 08	0,6	779 721 009	
60,3 - 63,0	779 724 010	013 45 09	0,6	779 721 010	013 46 03
66,6 - 70,0	779 724 011	013 45 10	1,4	779 721 011	
73,0 - 79,5	779 724 012	013 45 11	1,4	779 721 012	
84,0	779 724 013	013 45 12	1,6	779 721 013	
88,9	779 724 014	013 45 13	1,6	779 721 014	
98,0 - 104,0	779 724 015	013 45 14	1,7	779 721 015	
104,8 - 110,0	779 724 016	013 45 15	1,7	779 721 016	
114,3 - 118,0	779 724 017	013 45 16	1,9	779 721 017	
125,0 - 129,0	779 724 018	013 45 17	1,9	779 721 018	
130,2 - 133,0	779 724 019	013 45 18	3,4	779 721 019	
139,7 - 141,6	779 724 020	013 45 19	3,5	779 721 020	
154,0 - 155,0	779 724 021	013 45 20	3,6	779 721 021	
159,0	779 724 022	013 45 21	3,7	779 721 022	
165,0 - 168,3	779 724 023	013 45 22	3,8	779 721 023	

Ulkohalk. nimell. (mm)	M (bar)	PN (bar)	WP (bar)	C max. (mm)	Ulkohalk. min. (mm)	Ulkohalk. max. (mm)	d (mm)	B (mm)	H (mm)	Momentti (N/m)
21,3 - 21,6	M6	16	70	10	21,0	23,0	46	45	76	7
26,9 - 28,0	M6	16	70	10	26,0	29,0	46	45	76	7
30,0	M6	16	70	10	29,0	32,0	54	45	84	7
33,7 - 35,0	M6	16	70	10	33,0	36,0	54	45	84	7
38,0	M8	16	60	15	36,0	39,0	66	60	104	25
42,4	M8	16	50	15	39,0	43,0	66	60	104	25
44,5	M8	16	50	15	43,0	47,5	74	60	112	25
48,3	M8	16	50	15	47,5	52,5	74	60	112	25
54,0 - 57,0	M8	16	50	25	52,5	58,0	85	75	125	25
60,3 - 63,0	M8	16	40	25	58,0	64,0	85	75	125	25
66,6 - 70,0	M10	16	40	30	64,0	72,0	108	95	164	40
73,0 - 79,5	M10	16	40	30	72,0	80,0	108	95	164	40
84,0	M10	16	35	30	80,0	88,0	124	95	170	40
88,9	M10	16	35	30	88,0	96,0	124	95	170	40
98,0 - 104,0	M10	16	35	30	97,0	105,0	141	95	187	40
104,8 - 110,0	M10	16	35	30	104,0	112,0	141	95	187	40
114,3 - 118,0	M10	16	35	30	112,0	120,0	158	95	202	40
125,0 - 129,0	M10	16	32	30	122,0	130,0	158	95	202	40
130,2 - 133,0	M12	16	32	40	129,0	137,0	178	110	230	65



Ulkohalk. nimell. (mm)	M (bar)	PN (bar)	WP (bar)	C max. (mm)	Ulkohalk. min. (mm)	Ulkohalk. max. (mm)	d (mm)	B (mm)	H (mm)	Momentti (N/m)
139,7 - 141,6	M12	16	32	40	137,0	145,0	186	110	238	65
154,0 - 155,0	M12	16	32	40	149,0	157,0	197	110	249	65
159,0	M12	16	32	40	157,0	165,0	205	110	255	65
165,0 - 168,3	M12	16	32	40	164,0	172,0	212	110	262	65

Liitin UNI-Grip LE PN10

Rakenne :


- Runko, pultit ja insertit (lisävaruste): Haponkestävä teräs W5 (1.4571)

Lämpötila/Paine:

- Käyttölämpötila EPDM: -30°C - 125°C
- Käyttölämpötila NBR: -20°C - 80°C



Vaihtoehto:

- Viton-tyyppiset tiivisteet tilauksesta



Ulkohalk. nimell. (mm)	EPDM Koodi	LVI	Paino (kg)	NBR Koodi	LVI
66,6 - 70,0	779 724 411		1,0	779 721 411	
73,0 - 79,5	779 724 412	013 46 09	1,0	779 721 412	013 46 04
84,0	779 724 413		1,0	779 721 413	
88,9	779 724 414	013 46 10	1,0	779 721 414	013 46 05
98,0 - 104,0	779 724 415		1,1	779 721 415	
104,8 - 110,0	779 724 416		1,1	779 721 416	
114,3 - 118,0	779 724 417	013 46 11	1,2	779 721 417	013 46 06
125,0 - 129,0	779 724 418		1,2	779 721 418	
130,2 - 133,0	779 724 419		2,1	779 721 419	
139,7 - 141,6	779 724 420	013 46 12	2,2	779 721 420	013 46 07
154,0 - 155,0	779 724 421		2,3	779 721 421	
159,0	779 724 422		2,3	779 721 422	
165,0 - 168,3	779 724 423	013 46 13	2,4	779 721 423	013 46 08

Ulkohalk. nimell. (mm)	M (bar)	PN (bar)	WP (bar)	C max. (mm)	Ulkohalk. min. (mm)	Ulkohalk. max. (mm)	d (mm)	B (mm)	H (mm)	Momentti (N/m)
66,6 - 70,0	M10	10	16	30	64	72	108	95	164	40
73,0 - 79,5	M10	10	16	30	72	80	108	95	164	40
84,0	M10	10	16	30	80	88	124	95	170	40
88,9	M10	10	16	30	88	96	124	95	170	40
98,0 - 104,0	M10	10	16	30	97	105	141	95	187	40
104,8 - 110,0	M10	10	16	30	104	112	141	95	187	40
114,3 - 118,0	M10	10	16	30	112	120	158	95	202	40
125,0 - 129,0	M10	10	16	30	122	130	158	95	202	40
130,2 - 133,0	M12	10	16	40	129	137	178	110	230	65



Ulkohalk. nimell. (mm)	M (bar)	PN (bar)	WP (bar)	C max. (mm)	Ulkohalk. min. (mm)	Ulkohalk. max. (mm)	d (mm)	B (mm)	H (mm)	Momentti (N/m)
139,7 - 141,6	M12	10	16	40	137	145	186	110	238	65
154,0 - 155,0	M12	10	16	40	149	157	197	110	249	65
159,0	M12	10	16	40	157	165	205	110	255	65
165,0 - 168,3	M12	10	16	40	164	172	212	110	262	65