



NT 65/2 Ap *EU

Tehokas kaksimootorinen märkä-kuivaimuri ammattikäyttöön. Laakasuodattimen ansiosta maksimaalinen säiliökapasiteetti. Puoliautomaattinen suodattimen ravistus.

1 Hose and bend attachment

- Convenient suction hose and bend attachment for easy transport and storage.

3 Integrated drain hose (oil-resistant)

- Easily accessible drain hose for convenient liquid disposal.

2 On-board storage

- The large on-board storage space on the casing head ensures that tools and accessories are always stored and close to hand.

4 ApClean - puoliautomaattinen suodattimen puhdistus

- The free filter means that the user can work for long intervals without interruption.
- Optimal suction power with high efficiency.



NT 65/2 Ap *EU

Tekniset tiedot

Tuotenumero		1.667-291.0
EAN koodi		4039784727281
Ilman läpivirtaus	l/s	2 x 74
Alipaine	mbar / kPa	254 / 25,4
Säiliötilavuus	l	65
Maks. ottoteho	W	2760
Varusteiden halkaisija ID 51/61		40
Johdon pituus	m	10
Äänenvoimakkuus	dB(A)	73
Säiliön materiaali		Muovi
Moottoreiden lukumäärä		2
Taajuus	Hz	50-60
Jännite	V	220-240
Paino	kg	20
Mitat (p x l x k)	mm	600 x 480 x 920

Laite

Imuletku	m	4	Turvallisuusluokitus	II
Imutangot metallia, 2x 0,5 m	■		Kuljetuspyörä seisontajarrulla	■
Pölypussi	Paperi		Suodattimenpuhdistus	ApClean - puoliautomaattinen suodattimen puhdistus
Lattiasuutin markä- ja kuivaimurointiin	mm	360	Huoltovapaat imumoottorit	kpl 2
Rakosuutin	■			
Tyhjennysletku (öljynkestävä)	■			
Automaattinen pinnanvartija säiliön täyttyessä	■			
Laakasuo datin	Paperi			
Imukahvalla	■			
Puskuri	■			
Työntöaisa	■			

■ Toimituksen mukana.

VARUSTEET. NT 65/2 AP *EU

1.667-291.0

KÄRCHER


		Tuotenumero	Määrä		Pituus	Leveys	Kuvaus	
Laakasuodatin (paperi)								
Laakasuodatin NT 65/2Eco	1	6.904-283.0	1 kpl				Paper flat pleated filter (BIA-(U,S,G,C) dust class M) suitable for NT 65/2 Eco, NT 65/2 Eco Tc, NT 65/2 Eco Me.	■
Paperinen pölypusi (kaksinkertainen)								
PÖLYPUSSI NT 65/2 Eco	2	6.904-285.0	5 kpl				5 3-ply, tear-resistant paper filter bags. BIA-(U, S, G, C) dust class M. For all NT 48/1, NT 65/2 Eco + Me and NT 72/2 Eco Tc models.	■
Taivutettu imutanko, muovia								
Taivutettu tanko DN 40, muovi	3	5.031-904.0	1 kpl	ID 40			Plastic bend (DN 40) with C-40 clip system, suitable for all NT models.	■
Taivutettu tanko DN 35, muovi	4	5.031-718.0	1 kpl	ID 35			Plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models (except NT Eco M and NT Eco H).	□
Taivutettu tanko DN 35, muovi, sähköä johtava	5	5.031-939.0	1 kpl	ID 35			Electrically conductive plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models.	□
Taivutettu tanko DN 40, muovi, sähköä johtava	6	5.032-427.0	1 kpl	ID 40			Electrically conductive plastic bend (DN 40) with C-40 clip system, suitable for all NT vacuum cleaners.	□
Lattiasuulakkeet								
Floor tool packaged basalt grey DN40	7	6.907-408.0	1 kpl	ID 40		360 mm		■
LAITOSSUUTIN GRD 370	8	6.903-018.0	1 kpl	ID 40		370 mm	All-purpose aluminium nozzle with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	□
LATTIASUULAKE DN40	9	6.906-383.0	1 kpl	ID 40		450 mm	All-purpose aluminium nozzle (DN 40) with 450 mm working width. With height-adjustable side rollers, brush strips (6.903-065.0) and oil-resistant squeegees (6.906-146.0). Only for NT vacuum cleaners.	□
LATTIASUULAKE DN 35	10	6.906-384.0	1 kpl	ID 35		370 mm	All-purpose aluminium nozzle (DN 35) with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	□
LATTIASUULAKE DN35	11	6.906-513.0	1 kpl	ID 35		360 mm	All-purpose plastic nozzle (DN 35) with 360 mm working width. With side rollers, brush strips (6.905-878.0) and squeegees (6.905-877.0). Only for NT vacuum cleaners.	□
Rakosuulakkeet								
RAKOSUUTIN NW 40	12	6.903-033.0	1 kpl	ID 40	290 mm		Plastic crevice tool (DN 40) for vacuuming in crevices and corners. Length: 290 mm.	■
RAKOSUUTIN, NW 35	13	6.900-385.0	1 kpl	ID 35	210 mm		Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 210 mm.	□
RAKOSUUTIN METALLISTA	14	6.900-922.0	1 kpl	ID 35	500 mm		Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 370 mm.	□
RAKOSUUTIN	15	6.905-817.0	1 kpl	ID 40	400 mm		Metal crevice tool (DN 40) for vacuuming in crevices and corners. Length: 400 mm.	□
Imutangot metallia								
Imutanko, 0,5m, metallia/ ID 40	16	6.900-275.0	1 kpl	ID 40	0,5 m		Chromium-plated metal suction tube (DN 40, 1x0.5 m), standard for virtually all two-motor industrial vacuum cleaners. Optional for industrial single-motor NT vacuum cleaners with DN 40 suction hose.	■
IMUPUTKI NW 35, 0,5	17	6.900-514.0	1 kpl	ID 35	0,5 m		Chromium-plated metal suction tube (DN 35, 1x0.5 m), standard for virtually all single-motor industrial NT vacuum cleaners.	□

■ Toimituksen mukana. □ Saatavilla olevat varusteet.

VARUSTEET. NT 65/2 AP *EU

1.667-291.0

KÄRCHER



		Tuotenumero	Määrä		Pituus	Leveys	Kuvaus	
Imuletkut (Clip-system)								
Imuletku 4 m clip-system	18	6.906-321.0	1 kpl	40	4 m		4 m suction hose with bayonet and C 40 clip connection. Without bend and adapter.	■
Imuletku 10 m clip-system	19	6.906-279.0	1 kpl	40	10 m		10 m standard suction hose without bend and adapter. With bayonet at vacuum end and C 40 clip connection at accessory end.	□
Imuletku 4 m, öljyn kestävä, clip-system	20	6.906-714.0	1 kpl	40	4 m		With bayonet and clip connection.	□
Imuletku 4 m, clip-system, sähköä johtava	21	6.906-546.0	1 kpl	40	4 m		Sähköä johtava, 4 m imuletku bajonet-liitännällä ja C 40 clip-system pikakiinnityksellä. Mutka ja adapteri eivät sisälly toimitukseen. Huom! Ilman erillistä sovitinta, imuletku ei ole yhteensopiva 1-moottoristen imureiden vakiovarusteiden kanssa.	□
Imuletku 16 m, clip-system	22	6.906-635.0	1 kpl	40	16 m		With bayonet and clip connection.	□
Imuletku 4 m, clip-system, sähköä johtava	23	6.906-877.0	1 kpl	40	10 m		Suction hose with bayonet coupling, electrically conductive.	□
Imuletkut täydellinen (Clip-system)								
Imuletku 4 m, (Clip-system)	24	4.440-678.0	1 kpl	ID 40	4 m		4 m electrically non-conductive suction hose with bend, bayonet at vacuum end and C 40 clip connection at accessory end. Without module.	■
	25	4.440-679.0	1 kpl	ID 40	4 m		4 m electrically non-conductive suction hose with bend (C-DN 40) and module (4.060-474.0), bayonet at vacuum end and C 35 clip connection at accessory end.	□
Imuletku 4 m, (Clip-system), sähköä johtava	26	4.440-728.0	1 kpl	ID 40	4 m		With bend and module (4.060-533.0), electrically conductive.	□
Laakasuodatin (PES)								
Laakasuodatin, (PES), pölyluokka M	27	6.904-284.0	1 kpl				Flat filter (PES) - BIA-(U,S,G,C) dust class M: rotproof polyester fleece, ideal for wet use and abrasives. Standard for NT 72/2 Eco Tc.	□
Laakasuodatin (PTFE)								
Flat-pleated filter packaged PTFE	28	6.907-449.0	1 kpl					□
Kangassuodatin								
Membraanisuo-datin /polyester-fleece	29	6.904-282.0	1 kpl				Polyester needle fleece membrane/fabric filter - BIA-C -, washable up to 40°C, metal fibres for earthing. Suitable for virtually all industrial two-motor NT vacuum cleaners.	□
HEPA-suodatin, pölyluokka H								
HEPA laakasuodatin	30	6.904-364.0	1 kpl				HEPA surface filter - dust class H (H 14) - with glass-fibre layers increases filter capacity when vacuuming health-endangering and carcinogenic dust.	□
Muovisäkit								
Muovisäkki NT 7xx 110 kpl	31	6.900-698.0	10 kpl				PE plastic sack.	□
Erikoispölypussi, märkäimurointi								
Erikoispölypussi märkäimurointiin	32	6.904-252.0	5 kpl				Approved for dust class L, general cleaning, wet and dry, tear-resistant.	□
Taivutetut imutangot, rosteria								
Taivutettu tanko DN 35, RST	33	6.903-141.0	1 kpl	ID 35			Stainless steel and crooked, ID 35	□
Taivutettu tanko DN 40, RST	34	6.902-079.0	1 kpl	ID 40			Stainless steel and crooked, ID 40	□
Taivutetut imutangot, metallia								
Taivutettu tanko, metallia ID 35	35	6.900-519.0	1 kpl	ID 35			Robust, chromium-plated metal bend (DN 35), can be used instead of a plastic bend (with clip system adapter 5.407-112.0; C 35-DN 35, plastic, el.).	□

■ Toimituksen mukana. □ Saatavilla olevat varusteet.

VARUSTEET. NT 65/2 AP *EU

1.667-291.0

KÄRCHER


		Tuotenumero	Määrä		Pituus	Leveys		Kuvaus	
Taivutettu tanko, metallia ID 40	36	6.900-276.0	1 kpl	ID 40				Robust, chromium-plated metal bend (DN 40), can be used instead of a plastic bend (with clip system adapter 5.407-111.0; C 40-DN 40, plastic, el).	☐
Yleisharjat									
Yleisharjasuulake ID 35	37	6.903-863.0	1 kpl	ID 35	120 mm				☐
Autonimurointisuulakkeet									
AUTOSUUTIN,JATKOSSA 6.906-255	38	6.900-952.0	1 kpl	ID 40		90 mm		Angled, flat, plastic car vacuuming tool with about 90 mm working width. Only for NT vacuum cleaners.	☐
Kumisuulake									
Kumisuulake ID 40	39	4.763-057.0	1 kpl	40				Rubber.	☐
Imusuulake, kumikärki 45°									
Kumisuulake, DN 35 45° kärki	40	6.902-104.0	1 kpl	ID 35	220 mm			45° rubber suction nozzle (DN 35), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	☐
Kumisuulake, DN 40, 45° kärki	41	6.902-105.0	1 kpl	ID 40	220 mm			45° rubber suction nozzle (DN 40), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	☐
Harjasuulakkeet pattereille									
PATTERISUUTIN	42	6.903-034.0	1 kpl	ID 35				Radiator brush is suitable for crevice tool 6.900-385.0 or 6.905-240.0.	☐
Putkisuulakkeet									
PUTKISUUTIN 100 MM	43	6.903-035.0	1 kpl	ID 35				Plastic, pipe diameter 100 mm	☐
PUTKISUUTIN 200 MM	44	6.903-036.0	1 kpl	ID 35				Plastic, pipe diameter 200 mm	☐
Imutangot, ruostumaton teräs									
Imutanko, 0,5 m RST DN 40	45	6.902-081.0	1 kpl	ID 40	0,5 m			Stainless steel suction tube (DN 40, 0.5 m) only suitable for NT vacuum cleaners.	☐
Imutanko, 1 m RST DN 40	46	6.906-531.0	1 kpl	ID 40	1 m			Stainless steel suction tube (DN 40, 1.0 m) only suitable for NT vacuum cleaners.	☐
Imutanko DN 35	47	6.902-154.0	1 kpl	ID 35	0,5 m				☐
Imutangot muovi									
	48	6.900-224.0							☐
Jatkoputki, metallia									
	49	6.904-276.0	1 kpl	35	250 mm				☐
Korjaussarjat									
Korjaussetti	50	2.639-873.0	1 kpl	ID 40				Repair set (C40) includes threaded hose adapters (without bayonet adapter) for industrial NT vacuum cleaners with clip system.	☐
	51	2.862-038.0	1 kpl	ID 61				Suction hose repair kit. Optional for all NT 65/2 and 72/2, NT 993 I, NT 802 I.	☐
Imuletkut (ilman liittimiä)									
	52	6.389-838.0		32	10 m			Standard (not T 201 with ESB 28).	☐
	53	6.389-839.0						(without connectors)	☐
Imuletkut täydellinen									
Imuletku 4 m	54	4.440-264.0	1 kpl	ID 61	4 m			4-m standard suction hose with DN 61 bayonet connector at the device end and DN 61 tapered connector at the accessory end.	☐
Imuletku, teräsvahvistettu teollisuuslaatu	55	4.440-328.0	1 kpl	ID 61	3 m				☐
Imuletku 10 m	56	4.440-467.0	1 kpl	ID 61	10 m			10-m standard suction hose with DN 61 bayonet connector at the device end and DN 61 tapered connector at the accessory end.	☐
Imuletku 4 m, öljynkestävä	57	4.440-613.0	1 kpl	ID 61	4 m			Oil-resistant.	☐
Imuletku 10 m, öljynkestävä	58	4.440-614.0	1 kpl	ID 61	10 m				☐

■ Toimituksen mukana. □ Saatavilla olevat varusteet.

VARUSTEET. NT 65/2 AP *EU

1.667-291.0

KÄRCHER



		Tuotenumero	Määrä		Pituus	Leveys	Kuvaus	
Imuletku 4 m, sähköä johtava	59	4.440-616.0	1 kpl	ID 61	4 m			☐
Imuletku 4 m	60	4.440-263.0	1 kpl	ID 40	4 m		Electrically non-conductive 4.0m standard suction hose with bayonett at vacuum end and DN 40 cone at accessory end.	☐
Imuletku 4 m, öljynkestävä	61	4.440-303.0	1 kpl	ID 40	4 m		Oil-resistant	☐
Imuletku 10 m	62	4.440-463.0	1 kpl	ID 40	10 m		Electrically non-conductive 10.0m standard suction hose with bayonett at vacuum end and DN 40 cone at accessory end.	☐
Imuletku 10 m, sähköä johtava	63	4.440-466.0	1 kpl	ID 40	10 m		Electrically conductive, 10.0m, ID 40	☐
Imuletku 10 m, öljynkestävä	64	4.440-612.0	1 kpl	ID 40	10 m		Oil-resistant.	☐
Sovitinkappaleet								
Letkujen liitospäälle	65	4.453-006.0	1 kpl	ID 27				☐
	66	6.902-077.0	1 kpl	ID 32			Electrically non-conductive adapter with internal thread. For connecting two suction hoses without connectors. Suitable for DN 32 or DN 35.	☐
	67	6.900-286.0	1 kpl	ID 40			Electrically non-conductive adapter with screw thread at both ends. For connecting 2 DN 40 suction hoses without connectors.	☐
	68	6.902-078.0	1 kpl	ID 61				☐
Jatkoletkut (Clip-system)								
Jatkoletku (clip-system) 2,5 m	69	6.906-344.0	1 kpl	ID 40	2,5 m		2.5 m electrically non-conductive standard extension hose for all C-40 hoses with clip system.	☐
Sonstiges								
Esierotin	70	3.864-010.0	1 kpl					☐
Esierotin, metalli DN 61	71	3.864-012.0	1 kpl					☐
Kansi esierottimeen	72	4.063-132.0	1 kpl					☐
CS 40 Me	73	2.863-026.0	1 kpl					☐
Y-liitinsetti								
Y-kappalesetti, muovia	74	2.637-217.0	1 kpl	ID 35			Plastic distributor - suitable for NT vacuum cleaners.	☐
Sovitin C ID, antistaattinen								
Liitospäälle C-DN35 (sähköä johtava)	75	5.407-112.0	1 kpl	ID 35			C 35 hose connector for DN 35 accessory, electrically conductive.	☐
Liitospäälle C40-DN35	76	5.407-109.0	1 kpl	ID 40			Electrically conductive adapter (C 40) with DN 35 connection for connecting DN 35 accessories to an industrial C 40 or C-DN 40 suction hose. Suitable for NT vacuum cleaners.	☐
Liitospäälle C-DN40	77	5.407-111.0	1 kpl	ID 40			C 40 hose connector for DN 40 accessory, electrically conductive.	☐
Sovitin sähkötyökaluille, clip-kiinnitys, antistaattinen								
SÄHKÖTYÖKALUADAPTERI	78	5.453-042.0	1 kpl	ID 35			3-way plastic adapter. For DN 26 to DN 36. For connecting power tools to an industrial C or C-DN 35 suction hose. Suitable for NT vacuum cleaners.	☐
Liitospäälle, sähkötyökalulle	79	5.453-048.0	1 kpl	ID 35			Inside Ø 25.4 mm, outside Ø 34.6 mm/ 38 mm, electrically conductive. Only NT vacuums.	☐
	80	5.453-049.0	1 kpl	ID 35				☐
	81	5.453-050.0	1 kpl	ID 35			Inside Ø 27 mm, outside Ø 36.5 mm/38.8 mm, electrically conductive. Only NT vacuums.	☐
	82	5.453-051.0	1 kpl	ID 35				☐
	83	5.453-052.0	1 kpl	ID 35				☐

■ Toimituksen mukana. □ Saatavilla olevat varusteet.

VARUSTEET. NT 65/2 AP *EU

1.667-291.0

KÄRCHER


		Tuotenumero	Määrä		Pituus	Leveys		Kuvaus	
Sovitin sähkötyökaluille, kierteellä									
Adaptteri sähkötyökalulle	84	2.639-129.0	1 kpl	ID 35					☐
	85	5.453-016.0	1 kpl	ID 35				3-way plastic adapter with fitting instructions. For DN 26 to DN 36. For connecting to an industrial DN 35 suction hose.	☐
	86	5.453-026.0	1 kpl	ID 35				Inside Ø 28.6 mm, outside Ø 37.3/38.8 mm.	☐
	87	6.902-059.0	1 kpl	ID 35				Electrically conductive power tool adapter, threaded. Internal diameter: 32 mm. External diameter: 39 mm.	☐
	88	6.902-095.0	1 kpl	ID 35				2-way power tool adapter, threaded. For connecting to an industrial DN 35 suction hose. Internal diameter: 28 mm. External diameter: 34 mm and 38.8 mm. Suitable for NT vacuum cleaners.	☐
Sovitin (putkisuutin)									
Sovitin DN 40-61	89	5.453-019.0	1 kpl	ID 40				From DN 40 to DN 61: Plastic adapter (electrically non-conductive). Suitable for NT vacuum cleaners.	☐
Supistin									
Supistin C40	90	5.407-108.0	1 kpl	ID 40				Threaded reducer - from C-40 to DN 35. Suitable for NT vacuum cleaners.	☐
BUSHING	91	5.407-113.0	1 kpl	ID 40				Reducer (C 40 to C 35) for connecting accessories with C-35 clip connection to suction hoses with C 40 clip system.	☐
Supistin (putki - suutin)									
Supistin DN40 - DN35	92	6.902-017.0	1 kpl	ID 40				Reducer for accessory extension. Ideal for accessories with DN 35 connecting cone in combination with accessories with DN 40 connecting cone.	☐
Supistin DN35 - DN32	93	6.902-072.0	1 kpl	ID 35				Reducer with internal connecting cone DN 32. Ideal for accessories from the industrial vacuum cleaner range in combination with industrial NT vacuum cleaners.	☐
Supistin ja jatko-osasetti									
Supistin/sovitinsetti ID40/35, 35/32 muovia	94	2.860-117.0	1 kpl					DN 40/35, DN 35/32 (tube -> nozzle), plastic.	☐
Varustesetit imureihin									
Profi-setti ID 40	95	2.637-353.0		ID 40				Individual parts: Suction hose 4 m (4.440-263.0), bend, metal (6.900-276.0), suction tube 2 x 0.5 m, metal (6.900-275.0), grout nozzle (6.903-033.0), floor nozzle with rollers (6.903-051.0).	☐
Auton imurointiseti ID 36	96	2.862-166.0		ID 35				Target group-specific accessory nozzles in DN 35 for interior cleaning of vehicles, upholstery & fixtures.	☐
Teollisuussetti ID 61	97	2.637-355.0		ID 61				Target group-specific robust complete accessory set in DN 61 for vacuuming coarse dirt in industry, construction etc.	☐
Askarteluseti	98	2.640-760.0		ID 61					☐
Bussin imurointiseti ID 40 NT 65/2	99	2.640-560.0		ID 40				Accessory kit for vacuuming and cleaning buses, train compartments, etc., in combination with the recommended NT vacuum cleaner.	☐
UBS sähköä johtamaton									
	100	2.642-602.0	1 kpl						☐

■ Toimituksen mukana. □ Saatavilla olevat varusteet.

VARUSTEET. NT 65/2 AP *EU
1.667-291.0



		Tuotenumero	Pituus		Määrä		Kuvaus	
Sekalaiset								
Jatkojohto	1	6.647-022.0	20 m		1 kpl		Extension cable, 20 m, 3x1.5 mm ² . With splash-proof earthing pin plug, strain relief and anti-kink sleeve.	☐

■ Toimituksen mukana. ☐ Saatavilla olevat varusteet.

VARUSTEET. NT 65/2 AP *EU

1.667-291.0

KÄRCHER



		Tuotenumero	Määrä		Pituus/ Leveys		Kuvaus	
Lattiasuulakkeet								
Lattiasuulake 500 mm	1	4.130-413.0	1 kpl	ID 61	500 mm		Aluminium, oil-proof, 500 mm, with hight-adjustable rollers, strips (6.903-067.0) and rubber lips (6.906-168.1)	☐
Muut suulakkeet								
Kuminen suulake 45° DN61	2	6.902-106.0	1 kpl	ID 61	220 mm		Angled 45°, for suction of machines, oil-resistant	☐
Raaputin metallia	3	6.903-360.0	1 kpl	ID 61	104 mm		Scratcher and scraper tool DN 61, sheet metal, 117 mm	☐
Tasopintojen suulake alu DN 61 200 mm	4	4.130-415.0	1 kpl	ID 61	200 mm		Flat surface nozzle cpl. DN 51, 200 mm, aluminium with brush and stainless steel bumper	☐
Rakosuulakkeet								
Saumalaastisuulake 370 mm syn- teettinen	5	6.900-222.0	1 kpl	ID 61	370 x 64 mm		Grout nozzle, plastic, 370 mm	☐
Liittimet ja varaosat								
Vacuum cleaner connection DN61 auf DN52	6	6.902-002.0	1 kpl	ID 52				☐

■ Toimituksen mukana. □ Saatavilla olevat varusteet.