

CERTIFICATE OF CONFORMITY

Cable type: **FLEXIDRUM TD 210 C TP**

We confirm that the above mentioned cable is produced according to:

Conductor construction acc. to IEC 60228, DIN VDE 0295;
Color cores acc. to DIN 47100;
Halogen free acc. to IEC 60754-1, DIN VDE 0482 part.267-1, EN 50267-1;
Flame retardant acc. to IEC 60332-1, DIN VDE 0482 part.0482 part.265-2-1,
EN 50265-2-1, UL VW-1, CSA FT-1, CSA FT-2
Oil resistant acc. to IEC 60811-2-1, DIN VDE 0282 part.10, DIN VDE 0473 part 811-2-1
UL STYLE 21198 80°C 300 V CSA AWM I/II A/B 80°C 300 V FT1 FT2 or
UL STYLE 20223 80°C 300 V FT2 CE

Temperature range:

	DIN VDE	UL/CSA
-Fixed installation:	-50°C up to +90°C	up to +80°C
-Flexible installation:	-40°C up to +90°C	up to +80°C


Nominal voltage:

	DIN VDE	UL/CSA
-U ₀ /U:	300/500 V	300 V

acc. to RoHS-guideline 2002/95/EG as well as GefStoffV appendix IV-no. 24
CE: The product is conformed with the EC Low-Voltage Directive 2006/95/EC

WARRANTY PERIOD:

The warranty period is 24 months after delivery

Operator	Technical manager
 Andrea Fiorini	 Luca Bolondi