

## M18 ONEID2-0X | M18 FUEL™ ONE-KEY™ 1/4 Hex impact driver



- Higher power efficiency under load - outstanding torque of 226 Nm.
- Faster driving speed vs. previous model - up to 3600 rpm and 4300 ipm.
- Extreme compact design - total length of just 117 mm for access into tight spaces.
- Connect via Bluetooth® with the Milwaukee® ONE-KEY™ app.
- ONE-KEY™ app provides inventory function for total management of your complete tool/equipment fleet.
- Save up to 4 custom settings to the tools memory for fast selection on the jobsite.
- Configure to any application choosing optimum tool settings for repeatable precision.

	M18 ONEID2-0X
Battery pack capacity (Ah)	-
Battery type	Li-ion
Charger supplied	-
Impact rate (ipm)	1200/ 3400/4300/0-4300
Max. bolt diameter	M16
Max. fastening torque (Nm)	226
Max. torque (Nm)	119/176/226/0-226
No load speed (rpm)	1900/2800/3600/0-3600
No. of batteries supplied	0
Sound power level measured (dB(A))	107.75
Sound power level measured uncertainty (dB(A))	3
Sound pressure level (dB(A))	96.75
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Belt clip and bit holder
Supplied in	HD Box
Vibration Impact tightening of fasteners of the maximum capacity of the tool [m/s <sup>2</sup> ]	18.63
Vibration Impact tightening of fasteners of the maximum capacity of the tool uncertainty [m/s <sup>2</sup> ]	1.5
Voltage (V)	18
Weight with battery pack (kg)	-