

## M18 BSX-402C | M18™ SAWZALL®



- Milwaukee®'s high performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Milwaukee® patented FIXTEC clamp for fast and easy keyless blade change.
- Counter balance mechanism to reduce vibrations 15.2 m/s<sup>2</sup> in wooden beams.
- 28.6 mm stroke length & 3000 strokes per minute for extremely fast cutting.
- Fuel gauge displays remaining charge.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.

	M18 BSX-402C
Battery pack capacity (Ah)	4.0
Battery type	Li-ion
Charger supplied	80 min
Max. cutting depth in aluminium (mm)	25
Max. cutting depth in metal pipe (mm)	150
Max. cutting depth in non-ferrous metal (mm)	25
Max. cutting depth in soft-wood (mm)	300
Max. cutting depth in steel (mm)	20
No load stroke rate (spm)	3000
No. of batteries supplied	2
Sound power level measured (dB(A))	93,9
Sound power level measured uncertainty (dB(A))	3,0
Sound pressure level (dB(A))	82,9
Sound pressure level uncertainty (dB(A))	3,0
Standard equipment	Blade
Stroke length (mm)	28.6
Supplied in	Kitbox
Vibration cutting wooden beam (m/s <sup>2</sup> )	15,2
Vibration cutting wooden beam uncertainty (m/s <sup>2</sup> )	1,5
Vibration sawing of wood [m/s <sup>2</sup> ]	18,0
Vibration sawing of wood uncertainty [m/s <sup>2</sup> ]	1,5