

## AG 24-230 E | 2400 W angle grinder



- Powerful, 2400 W “PROTECTOR-MOTOR” with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool.
- Ergonomically designed motor housing for best user comfort.
- Soft start for smooth start up.
- Burst resistant quick release safety guard for easy adjustment.
- Automatic cut-off carbon brushes.
- 4 m rubber cable.

	AG 24-230 E
Anti-kickback protection	No
AVS Anti-Vibration System	No
Line lock out function	Yes
Max. cutting depth (mm)	68
No load speed (rpm)	6600
Power input (W)	2400
Rotatable main handle	No
Sound power level (dB(A))	105
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	93
Sound pressure level uncertainty (dB(A))	3
Spindle size	M 14
Standard equipment	Quick release safety guard, side handle, flange nut, wrench, 4 m cable
Supplied in	-
Variable speed	No
Vibration grinding (m/s <sup>2</sup> )	6
Vibration grinding uncertainty (m/s <sup>2</sup> )	1.5
Vibration sanding (m/s <sup>2</sup> )	<2.5
Vibration sanding uncertainty (m/s <sup>2</sup> )	1.5
Weight (kg)	5.3