

AG 9-125 XC | 850 W angle grinder



- Powerful, 850 W “PROTECTOR-MOTOR” with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool.
- Light weight, slim and compact: a versatile all-purpose angle grinder.
- New digital electronic pack offers constant speed, soft start, motor overload protection and no-load speed limitation.
- Flat metal gear head for excellent visibility of work piece and optimised cutting depth.
- Die-cast magnesium alloy gear case.
- Dust protected bearings and switch.
- Effective cooling fan keeps the motor cool even under heavy duty conditions.

	AG 9-125 XC
Anti-kickback protection	No
AVS Anti-Vibration System	No
Line lock out function	Yes
Max. cutting depth (mm)	33
No load speed (rpm)	10,000
Power input (W)	850
Sound power level (dB(A))	100
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	89
Sound pressure level uncertainty (dB(A))	3
Spindle size	M 14
Standard equipment	Quick release safety guard, side handle, flange, FIXTEC flange nut, 4 m cable
Supplied in	-
Variable speed	No
Vibration grinding (m/s ²)	10
Vibration grinding uncertainty (m/s ²)	1.5
Vibration sanding (m/s ²)	3.5
Vibration sanding uncertainty (m/s ²)	1.5
Weight (kg)	1.8