

AG 9-125 XE | 850 W angle grinder



- Powerful, 850 W “PROTECTOR-MOTOR” with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool.
- Light weight, slim and compact: a versatile all-purpose angle grinder.
- New digital electronic pack offers constant speed, soft start, motor overload protection and no-load speed limitation.
- Flat metal gear head for excellent visibility of work piece and optimised cutting depth.
- Die-cast magnesium alloy gear case.
- Dust protected bearings and switch.
- Effective cooling fan keeps the motor cool even under heavy duty conditions.

	AG 9-125 XE
Anti-kickback protection	No
AVS Anti-Vibration System	No
Disc diameter (mm)	125
Line lock out function	Yes
Max. cutting depth (mm)	33
No load speed (rpm)	2700 - 10,000
Power input (W)	850
Sound power level (dB(A))	100
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	89
Sound pressure level uncertainty (dB(A))	3
Spindle size	M 14
Standard equipment	Quick release safety guard, side handle, flange, FIXTEC flange nut, 4 m cable
Supplied in	-
Variable speed	Yes
Vibration grinding (m/s ²)	10
Vibration grinding uncertainty (m/s ²)	1.5
Vibration sanding (m/s ²)	3.5
Vibration sanding uncertainty (m/s ²)	1.5
Weight (kg)	1.8