

AGV 15-125 XC | 1550 W angle grinder with AVS



- Powerful, 1550 W “PROTECTOR-MOTOR” with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool.
- Very compact and slim design for comfortable handling.
- Soft start for smooth start up.
- Line lock out function to prevent automatic start up after power breakdown.
- Overload protection to prevent overheating.
- Safety clutch to protect the user from kickback injuries.
- New integrated and innovative FIXTEC tool-free disc change system.

| | AGV 15-125 XC |
|--|--|
| Anti-kickback protection | Yes |
| AVS Anti-Vibration System | Yes |
| Line lock out function | Yes |
| Max. cutting depth (mm) | 33 |
| No load speed (rpm) | 11,000 |
| Power input (W) | 1550 |
| Sound power level (dB(A)) | 97.5 |
| Sound power level uncertainty (dB(A)) | 3 |
| Sound pressure level (dB(A)) | 86.6 |
| Sound pressure level uncertainty (dB(A)) | 3 |
| Spindle size | M 14 |
| Standard equipment | Quick release safety guard, AVS side handle, flange, flange nut, 4 m cable |
| Supplied in | - |
| Variable speed | No |
| Vibration grinding (m/s ²) | 4.7 |
| Vibration grinding uncertainty (m/s ²) | 1.5 |
| Vibration sanding (m/s ²) | 4.5 |
| Vibration sanding uncertainty (m/s ²) | 1.5 |
| Weight (kg) | 2.6 |