

AGV 15-125 XE | 1550 W angle grinder with AVS



- Powerful, 1550 W “PROTECTOR-MOTOR” with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool.
- Very compact and slim design for comfortable handling.
- Soft start for smooth start up.
- Line lock out function to prevent automatic start up after power breakdown.
- Overload protection to prevent overheating.
- Safety clutch to protect the user from kickback injuries.
- New integrated and innovative FIXTEC tool-free disc change system.

	AGV 15-125 XE
Anti-kickback protection	Yes
AVS Anti-Vibration System	Yes
Disc diameter (mm)	125
Line lock out function	Yes
Max. cutting depth (mm)	33
No load speed (rpm)	2800 - 11,000
Power input (W)	1550
Sound power level (dB(A))	97.5
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	86.6
Sound pressure level uncertainty (dB(A))	3
Spindle size	M 14
Standard equipment	Quick release safety guard, AVS side handle, flange, flange nut, 4 m cable
Supplied in	-
Variable speed	Yes
Vibration grinding (m/s ²)	4.7
Vibration grinding uncertainty (m/s ²)	1.5
Vibration sanding (m/s ²)	4.5
Vibration sanding uncertainty (m/s ²)	1.5
Weight (kg)	2.6