

AGV 17-150 XC/DMS | 1750 W angle grinder with AVS



- Powerful, 1750 W “PROTECTOR-MOTOR” with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool.
- Constant power electronics with soft start for smooth start up.
- Line lock out function to prevent automatic start up after power breakdown.
- Thermal overload protection to prevent overheating.
- Safety clutch to protect the user from kickback injuries.
- FIXTEC nut for tool-free disc change.
- Burst resistant and tool-free safety guard for best user protection and fast adjustment.

AGV 17-150 XC/DMS	
Anti-kickback protection	Yes
AVS Anti-Vibration System	Yes
Disc diameter (mm)	150
Line lock out function	Yes
Max. cutting depth (mm)	45
No load speed (rpm)	9500
Power input (W)	1750
Sound power level (dB(A))	97.5
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	86.5
Sound pressure level uncertainty (dB(A))	3
Spindle size	M 14
Standard equipment	Quick release safety guard, AVS side handle, FIXTEC flange nut, flange nut, 4 m cable
Supplied in	-
Variable speed	No
Vibration grinding (m/s ²)	8.7
Vibration grinding uncertainty (m/s ²)	1.5
Vibration sanding (m/s ²)	3
Vibration sanding uncertainty (m/s ²)	1.5
Weight (kg)	3.0