

AGVM 24-230 GEX/DMS | 2400 W angle grinder with AVS and kickback protection



- Milwaukee® B-Guard protects both operator and machine from “kickback” effect.
- Powerful, 2400 W “PROTECTOR-MOTOR” with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool.
- Autobalancer for greatly reduced vibration of bad discs.
- AVS equipped motor housing and additional AVS side handle for more comfortable handling and less strain of body joints.
- Lowest vibration in it's class with only 2.5 m/s².
- 7 position rotatable main handle.
- FIXTEC flange nut for fast and easy change of discs.

AGVM 24-230 GEX/DMS	
Anti-kickback protection	Yes
AVS Anti-Vibration System	Yes
Disc diameter (mm)	230
Line lock out function	No
Max. cutting depth (mm)	68
No load speed (rpm)	6600
Power input (W)	2400
Rotatable main handle	Yes
Sound power level (dB(A))	104
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	93
Sound pressure level uncertainty (dB(A))	3
Spindle size	M 14
Standard equipment	Quick release safety guard, AVS side handle, Autobalancer, FIXTEC flange nut, 4 m cable
Supplied in	-
Variable speed	No
Vibration grinding (m/s ²)	2.5
Vibration grinding uncertainty (m/s ²)	1.5
Vibration sanding (m/s ²)	<2.5
Vibration sanding uncertainty (m/s ²)	1.5
Weight (kg)	5.8