

C18 RAD-0 | M18™ compact right angle drill



- Optimised performance: 1500 rpm at 20 Nm.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Perfect speed to power ratio for fast application completion.
- 10 mm single sleeve ratcheting chuck provides maximum versatility and grip.
- 100 mm compact head designed to fit in the tightest work areas.
- Multi-position handle design allows for multiple hand positions and maximum comfort.
- 10 + 1 electronic clutch enables complete control while fastening.

	C18 RAD-0
Battery pack capacity (Ah)	-
Battery type	Li-ion
Charger supplied	-
Chuck capacity (mm)	10
Max. drilling steel (mm)	10
Max. drilling wood (mm)	28
Max. torque (Nm)	20
No load speed (rpm)	0 - 1500
No. of batteries supplied	0
Sound power level (dB(A))	83
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	72
Sound pressure level uncertainty (dB(A))	3
Supplied in	-
Vibration drilling into Metal [m/s ²]	<2.5
Vibration drilling into metal uncertainty [m/s ²]	1.5
Vibration screw driving (m/s ²)	<2.5
Vibration screw driving uncertainty (m/s ²)	1.5
Voltage (V)	18
Weight (kg)	1.2
Weight with battery pack (kg)	1.9