

HD18 H-402C | M18™ 4-mode SDS-plus hammer



- High powered motor gives corded tool performance.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Powerful hammer mechanism: delivers 2.4 J (EPTA) of impact energy.
- All metal gear case: optimum seating for gears to enhance service life.
- 4-mode operation: rotary hammer, hammer only, rotation only and selectable work position of the chisel (variolock) for maximum versatility.
- Variolock and hammer stop function.
- Mechanical clutch: protects tool when bit binds up.

	HD18 H-402C
Battery pack capacity (Ah)	4.0
Battery type	Li-ion
Blow energy (EPTA)(J)	2.4
Charger supplied	80 min
Max. drilling concrete (mm)	24
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Max. percussion rate (bpm)	4200
No. of batteries supplied	2
Sound power level (dB(A))	99
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	88
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Side handle with metal depth gauge
Supplied in	Kitbox
Vibration chiseling (m/s ²)	7.4
Vibration chiselling uncertainty (m/s ²)	1.5
Vibration drilling (m/s ²)	12.2
Vibration drilling into concrete [m/s ²]	12.2
Vibration drilling into concrete uncertainty [m/s ²]	1.5
Voltage (V)	18
Weight with battery pack (kg)	3.5