

HD18 HX-O | M18™ 4-mode SDS-Plus hammer with FIXTEC chuck



- High powered motor gives corded tool performance.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Powerful hammer mechanism: delivers 2.4 J (EPTA) of impact energy.
- All metal gear case: optimum seating for gears to enhance service life.
- 4-mode operation: rotary hammer, hammer only, rotation only and variolock for maximum versatility.
- Variolock and hammer stop function.
- FIXTEC system - keyless chuck changing.

	HD18 HX-O
Battery pack capacity (Ah)	–
Battery type	Li-ion
Blow energy (EPTA)(J)	2.4
Charger supplied	–
Max. drilling concrete (mm)	24
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Max. percussion rate (bpm)	4200
No. of batteries supplied	0
Optimised drilling capacity in concrete (mm)	Ø 6 - 18
Sound power level (dB(A))	99
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	88
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Side handle with metal depth gauge, FIXTEC adaptor chuck
Supplied in	–
Vibration chiseling (m/s ²)	7.4
Vibration chiselling uncertainty (m/s ²)	1.5
Vibration drilling (m/s ²)	12.2
Vibration drilling into concrete [m/s ²]	12.2
Vibration drilling into concrete uncertainty [m/s ²]	1.5
Voltage (V)	18
Weight (kg)	3.0
Weight with battery pack (kg)	–