

M12 BID-202C | M12™ sub compact 1/4 Hex impact driver



- Milwaukee® high performance sub compact impact driver measures 165 mm in length making it ideal for working within confined spaces.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Heavy duty full metal gearbox and gears for superior durability and maximum torque.
- 1/4" Hex chuck for quick and easy bit change.
- Optimised handle for better control and improved grip.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions.

M12 BID-202C	
Battery pack capacity (Ah)	2.0
Battery type	Li-ion
Charger supplied	40 min
Impact rate (ipm)	0 - 3300
Max. torque (Nm)	112
No load speed (rpm)	0 - 2500
No. of batteries supplied	2
Sound power level (dB(A))	108
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	97
Sound pressure level uncertainty (dB(A))	3
Supplied in	Kitbox
Vibration screw driving (m/s²)	12.9
Vibration screw driving uncertainty (m/s²)	1.5
Voltage (V)	12
Weight with battery pack (kg)	1.0