

## M18 BH-402C | M18™ compact 2-mode SDS-plus hammer



- Superior power to weight ratio in its class 2.5 kg 1.2 J (EPTA).
- Milwaukee®'s high performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- 2-mode operation: choose rotary hammer or rotation only for maximum versatility.
- Low vibration value of 10.3 m/s<sup>2</sup>.
- Optimised hammer drilling from 4 to 10 mm, max diameter 16 mm.
- Forward & reverse switch for added versatility in fastening applications.

| M18 BH-402C                                                      |            |
|------------------------------------------------------------------|------------|
| Battery pack capacity (Ah)                                       | 4.0        |
| Battery type                                                     | Li-ion     |
| Blow energy (EPTA)(J)                                            | 1.2        |
| Blow energy (J)                                                  | 1.2        |
| Charger supplied                                                 | 80 min     |
| Max. drilling concrete (mm)                                      | 16         |
| Max. drilling steel (mm)                                         | 10         |
| Max. drilling wood (mm)                                          | 16         |
| Max. percussion rate (bpm)                                       | 7000       |
| No load speed (rpm)                                              | 0 - 1300   |
| No. of batteries supplied                                        | 2          |
| Optimised drilling capacity in concrete (mm)                     | Ø 5.5 - 13 |
| Sound power level (dB(A))                                        | 98.9       |
| Sound power level uncertainty (dB(A))                            | 3          |
| Sound pressure level (dB(A))                                     | 87.9       |
| Sound pressure level uncertainty (dB(A))                         | 3          |
| Supplied in                                                      | Kitbox     |
| Vibration drilling (m/s <sup>2</sup> )                           | 10.3       |
| Vibration drilling into concrete [m/s <sup>2</sup> ]             | 10.3       |
| Vibration drilling into concrete uncertainty [m/s <sup>2</sup> ] | 1.5        |
| Voltage (V)                                                      | 18         |
| Weight with battery pack (kg)                                    | 2.5        |