

M18 BRAID-O | M18™ right angle impact driver



- Compact right angle impact driver measures 307 mm in length making it ideal for working within confined spaces.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Full metal gearbox and gears for superior durability and maximum torque.
- Compact 53 mm head design.
- Multi-handle design for multiple hand positions and maximum comfort.
- 1/4" Hex chuck for quick easy one handed bit change.
- 2 speed settings for wider range of applications.

	M18 BRAID-O
Battery pack capacity (Ah)	—
Battery type	Li-ion
Charger supplied	—
Impact rate (ipm)	0 - 2400 / 0 - 3400
Max. torque (Nm)	41 / 81
No load speed (rpm)	0 - 1500 / 0 - 2250
No. of batteries supplied	0
Sound power level measured (dB(A))	101,6
Sound power level measured uncertainty (dB(A))	3
Sound pressure level (dB(A))	90,6
Sound pressure level uncertainty (dB(A))	3
Supplied in	—
Vibration Impact tightening of fasteners of the maximum capacity of the tool [m/s ²]	14,8
Vibration Impact tightening of fasteners of the maximum capacity of the tool uncertainty [m/s ²]	1,5
Voltage (V)	18
Weight with battery pack (kg)	1.8