

PD2E 22 R | 850 W 2-speed percussion drill



- Powerful 850 W motor.
- Electronics with variable speed selection and reverse function.
- AVS (Anti-Vibration-System) and soft grip for more comfortable use.
- Metal gearbox for outstanding durability.
- Direct bit reception for reduced length and weight for best visibility during screw driving.
- Safety clutch to protect the user.
- Keyless chuck 1.5 - 13 mm.

	PD2E 22 R
Chuck capacity (mm)	13
Max. drilling concrete (mm)	20
Max. drilling masonry (mm)	22
Max. drilling steel (mm)	13
Max. drilling wood (mm)	40
Max. percussion rate (bpm)	40,000
Max. static stalling torque (Nm)	56
No load speed gear 1 (rpm)	0 - 1000
No load speed gear 2 (rpm)	0 - 3200
Power input (W)	850
Sound power level (dB(A))	109
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	98
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Additional handle with metal depth gauge
Supplied in	Kitbox
Vibration drilling into concrete [m/s ²]	17.1
Vibration drilling into concrete uncertainty [m/s ²]	1.5
Vibration drilling into Metal [m/s ²]	7.6
Vibration drilling into metal uncertainty [m/s ²]	1.5
Weight (kg)	2.9