

PDE 13 RX | 630 W single speed percussion drill



- Excellent handling from a compact ergonomic design.
- IMB - Integrated-Metal-Block technology for highest durability and stability.
- Electronics: variable preselection of speed for optimum drilling.
- Hammer action stop for rotary drilling.
- Keyless chuck 1,5 - 13 mm with one sleeve.
- Easy access and exchange of carbon brushes by removing soft grip.
- 4 m cable.

	PDE 13 RX
Chuck capacity (mm)	13
Max. drilling concrete (mm)	15
Max. drilling masonry (mm)	18
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Max. static stalling torque (Nm)	21
No load speed (rpm)	0 - 2900
Power input (W)	630
Sound power level (dB(A))	95
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	84
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Additional side handle with metal depth gauge
Supplied in	Kitbox
Vibration drilling (m/s ²)	-
Vibration drilling into Metal [m/s ²]	3.5
Vibration drilling into metal uncertainty [m/s ²]	1.5
Vibration drilling uncertainty (m/s ²)	-
Weight (kg)	1.8