

## PDE 16 RP | 630 W single speed percussion drill



- Excellent handling from a compact ergonomic design.
- Planetary gearbox for low speed and high torque applications.
- Integrated-Metal-Block technology for highest durability and stability.
- Electronics: variable preselection of speed for optimum drilling.
- Hammer action stop for rotary drilling.
- 4 m cable.

	PDE 16 RP
Chuck capacity (mm)	13
Max. drilling concrete (mm)	16
Max. drilling masonry (mm)	20
Max. drilling steel (mm)	13
Max. drilling wood (mm)	40
Max. static stalling torque (Nm)	59
No load speed (rpm)	0 - 950
Power input (W)	630
Sound power level (dB(A))	111
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	100
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Additional side handle with metal depth gauge
Supplied in	Kitbox
Vibration drilling (m/s <sup>2</sup> )	<2.5
Vibration drilling into Metal [m/s <sup>2</sup> ]	25
Vibration drilling into metal uncertainty [m/s <sup>2</sup> ]	1.5
Vibration drilling uncertainty (m/s <sup>2</sup> )	1.5
Weight (kg)	2.0