

PFH 24 E | 24 mm SDS-plus 2-mode fixing hammer



- Variable speed - precise drilling start and perfect adjustment to the application.
- Lock-on switch for more comfortable extended use.
- Safety clutch protects machine and user if drill bit jams.
- Reverse function.
- Hammer stop function - turns off the hammering action - for screw driving applications or drilling without percussion in wood/metal.
- Service hatch - access hatch for servicing (e.g. worn-out carbon brushes).
- Depth-gauge knob.

	PFH 24 E
Blow energy (EPTA)(J)	1.9
Full load hammer action (bpm)	0 - 3700
Full load speed (soft hammer) (rpm)	0 - 850
Max. drilling masonry (mm)	24
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Power input (W)	670
Sound power level (dB(A))	100.5
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	89.5
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Front handle, depth gauge
Supplied in	Kitbox
Vibration drilling (m/s ²)	15.5
Vibration drilling into concrete [m/s ²]	15.5
Vibration drilling into concrete uncertainty [m/s ²]	1.5
Weight (kg)	2.4