

PH 26 | 26 mm SDS-plus 3-mode hammer



- Most compact, slimline hammer available in its class.
- Unmatched performance with 2.4 J blow energy and 4500 bpm.
- Lowest vibration only 13.5 m/s².
- Extreme Milwaukee® durability thanks to integrated metal block technology.
- Innovative and patented internal weight reduction technology.
- Hammer stop function.
- Safety clutch protects machine and user if drill bit jams.

	PH 26
Blow energy (EPTA)(J)	2.4
Full load hammer action (bpm)	0 - 4500
Full load speed (rpm)	0 - 1250
Max. drilling concrete (mm)	26
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Power input (W)	725
Sound power level (dB(A))	103
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	92
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Side handle with depth gauge
Supplied in	Kitbox
Vibration chiseling (m/s ²)	11.2
Vibration chiselling uncertainty (m/s ²)	1.5
Vibration drilling (m/s ²)	13.5
Vibration drilling into concrete [m/s ²]	13.5
Vibration drilling into concrete uncertainty [m/s ²]	1.5
Weight (kg)	2.4