

## SB 2-35 D | 1010 W 2-speed percussion drill



- Powerful 1010 W motor.
- High torque and lower speed for tough applications.
- Variable speed.
- Metal gearbox for outstanding durability.
- Hammer action stop for rotary drilling only.
- 16 mm metal keyed chuck.
- 4 m cable.

SB 2-35 D	
Chuck capacity (mm)	16
Max. drilling concrete (mm)	35
Max. drilling masonry (mm)	40
Max. drilling steel (mm)	16
Max. drilling wood (mm)	50
Max. static stalling torque (Nm)	57
No load speed gear 1 (rpm)	0 - 800
No load speed gear 2 (rpm)	0 - 1800
Power input (W)	1010
Sound power level (dB(A))	111
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	100
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Additional handle with metal depth gauge
Supplied in	Kitbox
Vibration drilling (m/s <sup>2</sup> )	17.8
Vibration drilling into Metal [m/s <sup>2</sup> ]	4.8
Vibration drilling into metal uncertainty [m/s <sup>2</sup> ]	1.5
Vibration drilling uncertainty (m/s <sup>2</sup> )	1.5
Weight (kg)	4.2