

## M12 BRAID-O | M12™ sub compact right angle impact driver



- Compact right angle impact driver measures 287 mm in length making it ideal for working within confined spaces.
- REDLINK™ overload protection electronics delivers best in class system durability.
- Full metal gearbox and gears for superior durability and maximum torque of 68 Nm.
- Compact head design with diameter of 35.6 mm.
- Multi-handle design for multiple hand positions and maximum comfort.
- 1/4" Hex chuck for quick easy one handed bit change.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.

M12 BRAID-O	
Battery pack capacity (Ah)	-
Battery type	Li-ion
Charger supplied	-
Impact rate (ipm)	0 - 3300
Max. fastening torque (Nm)	68
Max. torque (Nm)	68
No load speed (rpm)	0 - 2425
No. of batteries supplied	0
Sound power level measured (dB(A))	102.9
Sound power level measured uncertainty (dB(A))	3
Sound pressure level (dB(A))	91.9
Sound pressure level uncertainty (dB(A))	3
Supplied in	-
Vibration Impact tightening of fasteners of the maximum capacity of the tool [m/s <sup>2</sup> ]	11
Vibration Impact tightening of fasteners of the maximum capacity of the tool uncertainty [m/s <sup>2</sup> ]	1.5
Voltage (V)	12
Weight with battery pack (kg)	1.2