

M18 ONEDD-0X | ONE-KEY™ FUEL™ drill driver



- M18 FDD but with ONE-KEY™ technology.
- Connect via Bluetooth® with the Milwaukee® ONE-KEY™ app.
- Complete tool customisation via ONE-KEY™ app to tune the tool to your needs.
- Control speed, torque, start and end speeds, anti-kickback functions and LED.
- Configure to any application choosing optimum tool settings for repeatable precision.
- Program/save profiles for unmatched control.
- Select from a range of application profiles or quickly create your own for perfect results on every trigger pull.

| | M18 ONEDD-0X |
|---|------------------------|
| Battery pack capacity (Ah) | - |
| Battery type | Li-ion |
| Charger supplied | - |
| Chuck capacity (mm) | 13 |
| Max. drilling steel (mm) | 13 |
| Max. drilling wood (mm) | 45 |
| Max. torque (Nm) | 135 |
| No load speed gear 1 (rpm) | 0 - 550 |
| No load speed gear 2 (rpm) | 0 - 2000 |
| No. of batteries supplied | 0 |
| Sound power level measured (dB(A)) | 85.5 |
| Sound power level measured uncertainty (dB(A)) | 3 |
| Sound pressure level (dB(A)) | 74.5 |
| Sound pressure level uncertainty (dB(A)) | 3 |
| Standard equipment | Belt Clip, Side Handle |
| Supplied in | HD Box |
| Vibration drilling into Metal [m/s ²] | 1.29 |
| Vibration drilling into metal uncertainty [m/s ²] | 1.5 |
| Vibration screw driving (m/s ²) | 1.33 |
| Vibration screw driving uncertainty (m/s ²) | 1.5 |
| Voltage (V) | 18 |
| Weight with battery pack (kg) | - |