

## M12 BDDXKIT-202C | M12™ sub compact drill driver with removable chuck



- Milwaukee® high performance sub compact 5-in-1 drill driver system for extreme versatility.
- Removable chuck system with 3 different heads for multiples of applications.
- Standard 10 mm keyless chuck, full metal right angle 1/4" hex drive head and full metal offset 1/4" hex drive head.
- 1/4" hex drive behind chuck fitting, reduces drill length to 153 mm when required.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Full metal planetary gearbox transmission for extreme durability.
- LED light for workspace illumination.

M12 BDDXKIT-202C	
Battery pack capacity (Ah)	2.0
Battery type	Li-ion
Charger supplied	40 min
Chuck capacity (mm)	10
Max. drilling steel (mm)	10
Max. drilling wood (mm)	25
Max. torque (Nm)	32
No load speed gear 1 (rpm)	0 - 400
No load speed gear 2 (rpm)	0 - 1500
No. of batteries supplied	2
Sound power level (dB(A))	96
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	85
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Removable FIXTEC chuck, offset attachment, right angle drill attachment, belt clip, 25 mm PZ2 bit
Supplied in	Kitbox
Vibration drilling into Metal [m/s <sup>2</sup> ]	1.5
Vibration drilling into metal uncertainty [m/s <sup>2</sup> ]	1.5
Vibration screw driving (m/s <sup>2</sup> )	0.4
Vibration screw driving uncertainty (m/s <sup>2</sup> )	1.5
Voltage (V)	12
Weight with battery pack (kg)	1.2
Wood screws to (mm)	6