

M18 ONERSAL-0 | M18™ ONE-KEY™ LED remote stand light



- Optimise brightness and run time by adjusting the light output from 0 - 5400 Lumens.
- ONE-KEY™ tool customisation allows user to control brightness and set light settings remotely.
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention.
- IP67 allows use in all weather conditions (heavy rain, snow, dusty environments).
- Reinforced leg design with 3 different leg deployment options for best durability and stability.
- Highly durable and impact resistant polycarbonate lens and all aluminium cam design to protect the light from rough working conditions.
- TRUEVIEW™ high definition light output delivers consistent beam, optimised colour temperature and true representation of colours and detail.

M18 ONERSAL-0	
Battery compatibility	All Milwaukee® M18™ batteries
Battery pack capacity (Ah)	—
Battery type	Li-ion
Charger supplied	—
IP protection class	IP67
Max. light output High/Medium/Low/Strobe (Lumens)	5400/3000/1550/-
Max. run time with M18 B9 battery (h)	7/12.5/26/-
No. of batteries supplied	0
Supplied in	—
System	M18
Voltage (AC) (V)	—
Voltage (DC) (V)	18
Voltage (V)	18
Weight with battery pack (kg)	9.1