

## M18 ONEFHIWP12-0X | M18 FUEL™ ONE-KEY™ 1/2" high torque impact wrench with pin detent



- The M18 FUEL™ high torque impact wrench with ONE-KEY™ technology delivers 1017 Nm of fastening torque in a compact size of 206 mm, which gives more access in tight spaces.
- The 4 -Mode DRIVE CONTROL™ allows the user to shift into four different speed and torque settings to maximise application versatility.
- Mode 4 bolt removal, provides a maximum nut-busting torque of 1491 Nm then shifts to 750 rpm for unmatched control when removing fasteners.
- The integrated blow counting sensor enhances the consistent repeatability of the chosen torque setting.
- ONE-KEY™ tool customisation allows the user to optimise their tool for specific applications.
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention.
- 1/2" pin detent for maximum socket retention.

	M18 ONEFHIWP12-0X
Battery pack capacity (Ah)	-
Battery type	Li-ion
Charger supplied	-
Impact rate (ipm)	0-1150/0-2100/0-2400/0-2400
Max. bolt diameter	M24
Max. fastening torque (Nm)	190/400/1017/1017
No load speed (rpm)	0-950/0-1500/0-1800/0-1800
No. of batteries supplied	0
Nut-busting torque (Nm)	1491
Sound power level measured (dB(A))	105.7
Sound power level measured uncertainty (dB(A))	3
Sound pressure level (dB(A))	94.7
Sound pressure level uncertainty (dB(A))	3
Supplied in	HD Box
Vibration Impact tightening of fasteners of the maximum capacity of the tool [m/s <sup>2</sup> ]	18.4
Vibration Impact tightening of fasteners of the maximum capacity of the tool uncertainty [m/s <sup>2</sup> ]	1.5
Voltage (V)	18
Weight with battery pack (kg)	-