

M18 ONEFHIWF12-502X | M18 FUEL™ ONE-KEY™ 1/2 high torque impact wrench with friction ring



- The M18 FUEL™ high torque impact wrench with ONE-KEY™ technology delivers 1356 Nm of fastening torque in a compact size of 213 mm, which gives more access in tight spaces.
- The 4 -Mode DRIVE CONTROL™ allows the user to shift into four different speed and torque settings to maximise application versatility.
- Mode 4 bolt removal, provides a maximum nut-busting torque of 1898 Nm then shifts to 750 rpm for unmatched control when removing fasteners.
- The integrated blow counting sensor enhances the consistent repeatability of the chosen torque setting.
- ONE-KEY™ tool customisation allows the user to optimise their tool for specific applications.
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention.
- 1/2" friction ring reception.

| M18 ONEFHIWF12-502X | |
|-------------------------------|----------------------------|
| Battery pack capacity (Ah) | 5.0 |
| Battery type | Li-ion |
| Charger supplied | 59 min |
| Impact rate (ipm) | 0-950/0-1750/0-2100/0-2100 |
| Max. bolt diameter | M33 |
| Max. fastening torque (Nm) | 130/400/1356/1356 |
| No load speed (rpm) | 0-550/0-1400/0-1750/0-1750 |
| No. of batteries supplied | 2 |
| Nut-busting torque (Nm) | 1898 |
| Supplied in | HD Box |
| Voltage (V) | 18 |
| Weight with battery pack (kg) | 3.3 |