

## M18 ONEFHIWF34-502X | M18 FUEL™ ONE-KEY™ 3/4" high torque impact wrench with friction ring



- The M18 FUEL™ high torque impact wrench with ONE-KEY™ technology delivers 1627 Nm of fastening torque in a compact size of 213 mm, which gives more access in tight spaces.
- The 4 -Mode DRIVE CONTROL™ allows the user to shift into four different speed and torque settings to maximise application versatility.
- Mode 4 bolt removal, provides a maximum nut-busting torque of 2034 Nm then shifts to 750 rpm for unmatched control when removing fasteners.
- The integrated blow counting sensor enhances the consistent repeatability of the chosen torque setting.
- ONE-KEY™ tool customisation allows the user to optimise their tool for specific applications.
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention.
- 3/4" friction ring reception.

| M18 ONEFHIWF34-502X           |                            |
|-------------------------------|----------------------------|
| Battery pack capacity (Ah)    | 5.0                        |
| Battery type                  | Li-ion                     |
| Charger supplied              | 59 min                     |
| Impact rate (ipm)             | 0-850/0-1850/0-2400/0-2400 |
| Max. bolt diameter            | M33                        |
| Max. fastening torque (Nm)    | 1627                       |
| No load speed (rpm)           | 0-800/0-1300/0-1800/0-1800 |
| No. of batteries supplied     | 2                          |
| Nut-busting torque (Nm)       | 0-702/0-1138/0-1627/0-2034 |
| Supplied in                   | HD Box                     |
| Voltage (V)                   | 18                         |
| Weight with battery pack (kg) | 3.5                        |