

SSPE 1500 X | 1500 W Super SAWZALL®



- 1500 W Milwaukee® motor - highest overload protection in the industry; prevents motor burn up/failure.
- Constant power technology - maintains constant speed under load for unmatched cutting performance.
- Patented gear protecting clutch - extends gear and motor life by absorbing high impact forces caused by sudden blade lock-ups.
- FIXTEC blade clamp system - provides fast and easy blade changes.
- Patented AVS Anti-Vibration-System ensures unsurpassed low-vibration running at 12.5 m/s².
- Variable speed trigger and dial speed control - maximum speed control.
- Adjustable shoe for optimised use of saw blades.

	SSPE 1500 X
Length (mm)	477
No load stroke rate (spm)	0 - 2800
Power input (W)	1500
Sound power level (dB(A))	102
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	91
Sound pressure level uncertainty (dB(A))	3
Standard equipment	4 m cable, 1 SAWZALL® blade, additional keyed blade clamp
Stroke length (mm)	32
Supplied in	Kitbox
Vibration cutting boards (m/s ²)	15,2
Vibration cutting boards uncertainty (m/s ²)	1,6
Vibration cutting wooden beam (m/s ²)	19,9
Vibration cutting wooden beam uncertainty (m/s ²)	2,2
Weight (kg)	4.5