

MS 216 SB | 8 1/2" (216 mm) sliding mitre saw



- 1800 Watt motor for high performance cutting in hard timber.
- Durability - dual vertical steel rails with linear bearings deliver smooth sliding action.
- Rail lock - the saw head locks in the back position automatically.
- Adjustable laser - for perfect and quick alignment to cut line.
- Steel detent plate with preset angles - gives repeatable accurate cuts.
- Lock lever/handle over mold - allows the user to make repeated cuts comfortably and without fatigue.
- Mitre release system - for quick and smooth change of cutting orientation.

	MS 216 SB
Bevel capacity left (°)	48
Bevel capacity right (°)	-2
Blade diameter (mm)	216
Bore size (mm)	30
Max. cutting capacity 45° mitre/ 45° bevel (mm)	190 x 48
Max. cutting capacity 45° mitre/ 90° bevel (mm)	190 x 60
Max. cutting capacity 90° mitre/ 45° bevel (mm)	270 x 48
Max. cutting capacity 90° mitre/ 90° bevel (mm)	270 x 60
Mitre capacity left (°)	50
Mitre capacity right (°)	50
Mitre saw capacity 45° (mm)	190
Mitre saw capacity 90° (mm)	270
No load speed (rpm)	6000
Power input (W)	1800
Sound power level (dB(A))	105.5
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	92.5
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Saw blade (48 teeth), blade spanner, work clamp
Supplied in	-
Vibration cutting (m/s ²)	3.2
Vibration cutting uncertainty (m/s ²)	1.5
Weight (kg)	14.5