

M12 CHZ-402C | M12 FUEL™ sub compact hackzall™



- Milwaukee® designed and built brushless POWERSTATE™ motor for up to 6x longer motor life and up to 70% faster cutting in certain applications.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Milwaukee® patented FIXTEC clamp for fast and easy keyless blade change.
- Counter balance mechanism lowers vibration to 6.5 m/s² allowing the operator to work safely for longer periods of time reducing fatigue.
- Sealed gearbox prevents water and debris entering the housing.

	M12 CHZ-402C
Battery pack capacity (Ah)	4.0
Battery type	Li-ion
Charger supplied	80 min
No load stroke rate (spm)	0 - 3000
No. of batteries supplied	2
Sound power level (dB(A))	93.9
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	82.9
Sound pressure level uncertainty (dB(A))	3
Standard equipment	1 x Sawzall® blade
Stroke length (mm)	15.9
Supplied in	Kitbox
Vibration cutting (m/s ²)	5.7
Vibration cutting boards (m/s ²)	5.7
Vibration cutting boards uncertainty (m/s ²)	1.5
Vibration cutting uncertainty (m/s ²)	1.5
Vibration cutting wooden beam (m/s ²)	6.52
Vibration cutting wooden beam uncertainty (m/s ²)	1.5
Voltage (V)	12
Weight with battery pack (kg)	1.6