

# M18 BH-0 | M18™ compact 2-mode SDS-plus hammer



- Superior power to weight ratio in its class 2.5 kg 1.2 J (EPTA).
- Milwaukee®'s high performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- 2-mode operation: choose rotary hammer or rotation only for maximum versatility.
- Low vibration value of 10.3 m/s<sup>2</sup>.
- Optimised hammer drilling from 4 to 10 mm, max diameter 16 mm.
- Forward & reverse switch for added versatility in fastening applications.

	M18 BH-0
Battery pack capacity (Ah)	—
Battery type	Li-ion
Blow energy (EPTA)(J)	1.2
Blow energy (J)	1.2
Charger supplied	—
Max. drilling concrete (mm)	16
Max. drilling steel (mm)	10
Max. drilling wood (mm)	16
Max. percussion rate (bpm)	7000
No load speed (rpm)	0 - 1300
No. of batteries supplied	0
Optimised drilling capacity in concrete (mm)	ø 5.5 - 13
Sound power level (dB(A))	98.9
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	87.9
Sound pressure level uncertainty (dB(A))	3
Supplied in	—
Vibration drilling (m/s <sup>2</sup> )	10.3
Vibration drilling into concrete [m/s <sup>2</sup> ]	10.3
Vibration drilling into concrete uncertainty [m/s <sup>2</sup> ]	1.5
Voltage (V)	18
Weight with battery pack (kg)	—