

## M18 SMS216-0 | M18™ 216 mm mitre saw



- Milwaukee® powerful frameless motor delivers 2700 rpm for fast cutting.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Accuracy and durability are achieved with dual vertical steel rails with linear bearings which deliver smooth sliding action.
- Rail lock - the saw head locks in the back position automatically.
- Adjustable laser - for perfect and quick alignment to cut line.
- Steel detent plate with preset angles - gives repeatable accurate cuts.
- Lock lever/handle over mold - allows the user to make repeated cuts comfortably and without fatigue.

	M18 SMS216-0
Battery pack capacity (Ah)	—
Battery type	Li-ion
Bevel capacity left (°)	48
Bevel capacity right (°)	-2
Blade diameter (mm)	216
Bore size (mm)	30
Charger supplied	—
Max. cutting capacity 45° mitre/ 45° bevel (mm)	190 x 48
Max. cutting capacity 45° mitre/ 90° bevel (mm)	190 x 60
Max. cutting capacity 90° mitre/ 45° bevel (mm)	270 x 48
Max. cutting capacity 90° mitre/ 90° bevel (mm)	270 x 60
Mitre capacity left (°)	50
Mitre capacity right (°)	50
No load speed (rpm)	2700
No. of batteries supplied	0
Sound power level (dB(A))	101
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	88
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Blade, blade spanner, work clamp
Supplied in	—
Vibration sawing of wood [m/s <sup>2</sup> ]	1.9
Vibration sawing of wood uncertainty [m/s <sup>2</sup> ]	1.5