

HD28 PD-502C | M28™ percussion drill



- With its Milwaukee® high powered motor it delivers a staggering 90 Nm of torque, ideal for powering through the toughest of applications.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- All metal gear case provides maximum durability.
- Compact size of only 237 mm overall length.
- 13 mm Röhms chuck provides maximum durability.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.

	HD28 PD-502C
Battery pack capacity (Ah)	5.0
Battery type	Li-ion
Charger supplied	90 min
Chuck capacity (mm)	13
Max. drilling concrete (mm)	20
Max. drilling steel (mm)	16
Max. drilling wood (mm)	65
Max. torque (Nm)	90
No load speed gear 1 (rpm)	0 - 450
No load speed gear 2 (rpm)	0 - 1800
No. of batteries supplied	2
Sound power level (dB(A))	97.5
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	86.5
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Side handle
Supplied in	Kitbox
Vibration drilling into concrete [m/s ²]	11.6
Vibration drilling into concrete uncertainty [m/s ²]	1.5
Vibration drilling into Metal [m/s ²]	<2.5
Vibration drilling into metal uncertainty [m/s ²]	1.5
Vibration screw driving (m/s ²)	<2.5
Vibration screw driving uncertainty (m/s ²)	1.5
Voltage (V)	28