

## C12 MT-202B | M12™ sub compact multi-tool



- Versatile cordless solution for cutting and removal applications.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Variable speed (5000 - 20,000 rpm) and 1.5° left/right oscillation movement allows quick completion of professional applications into materials such as metal, wood and plastic.
- Will accept competitor accessories.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.

	C12 MT-202B
Battery pack capacity (Ah)	2.0
Battery type	Li-ion
Charger supplied	40 min
No load speed (rpm)	5000 - 20,000
No. of batteries supplied	2
Oscillation angle left/ right (°)	1.5
Sound power level (dB(A))	86.5
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	76.5
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Hex wrench, 1 x adapter, 1 x plunge cut blade OSC 112, 1 x sanding backing pad, 3 x grit 60, 3 x grit 80, 3 x grit 120, 3 x grit 240
Supplied in	Tool bag
Vibration cutting wood (m/s <sup>2</sup> )	8.7
Vibration cutting wood uncertainty (m/s <sup>2</sup> )	1.5
Vibration sanding (m/s <sup>2</sup> )	3.2
Vibration sanding uncertainty (m/s <sup>2</sup> )	1.5
Voltage (V)	12
Weight with battery pack (kg)	1.0