

C12 MT-402B | M12™ sub compact multi-tool



- Versatile cordless solution for cutting and removal applications.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Variable speed (5000 - 20,000 rpm) and 1.5° left/right oscillation movement allows quick completion of professional applications into materials such as metal, wood and plastic.
- Will accept competitor accessories.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.

| | C12 MT-402B |
|--|--|
| Battery pack capacity (Ah) | 4.0 |
| Battery type | Li-ion |
| Charger supplied | 80 min |
| No load speed (rpm) | 5000 - 20,000 |
| No. of batteries supplied | 2 |
| Oscillation angle left/ right (°) | 1.5 |
| Sound power level (dB(A)) | 86.5 |
| Sound power level uncertainty (dB(A)) | 3 |
| Sound pressure level (dB(A)) | 76.5 |
| Sound pressure level uncertainty (dB(A)) | 3 |
| Standard equipment | Hex wrench, 1 x adapter, 1 x plunge cut blade OSC 112, 1 x sanding backing pad, 3 x grit 60, 3 x grit 80, 3 x grit 120, 3 x grit 240 |
| Supplied in | Tool bag |
| Vibration cutting wood (m/s ²) | 8.7 |
| Vibration cutting wood uncertainty (m/s ²) | 1.5 |
| Vibration sanding (m/s ²) | 3.2 |
| Vibration sanding uncertainty (m/s ²) | 1.5 |
| Voltage (V) | 12 |
| Weight with battery pack (kg) | 1.2 |