

DD 2-160 XE | 2-speed dry diamond drill



- Powerful robust motor delivers constant high torque.
- Dual protection from the interlinked mechanical and electronic clutches to protect both user and tool.
- Robust construction with metal gearbox.
- Safe handling from the long AVS side handle and "D- shaped" back handle.
- 2-speed gear box.
- M16 FIXTEC adaptor for fast core bit changing.
- Soft hammer action - when activated allows the core bit to cut faster and easier.

	DD 2-160 XE
Chuck capacity (mm)	162
Full load speed (rpm)	0 - 890 / 0 - 1770
Max. drilling masonry (mm)	162
Max. static stalling torque (Nm)	50
No load hammer stroke (rpm)	24,000 / 48,000
No load speed (rpm)	0 - 1500 / 0 - 3000
Power input (W)	1500
Sound power level (dB(A))	111
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	100
Sound pressure level uncertainty (dB(A))	3
Supplied in	Kitbox
Vibration drilling (m/s ²)	13
Vibration drilling into concrete [m/s ²]	20
Vibration drilling into concrete uncertainty [m/s ²]	1.5
Vibration drilling into Metal [m/s ²]	<2.5
Vibration drilling into metal uncertainty [m/s ²]	1.5
Vibration drilling uncertainty (m/s ²)	3.6
Weight (kg)	4.2