

## M12 BPS-0 | M12™ sub compact polisher / sander



- Variable 2 speed selection (0-2800 / 0-8300 RPM) for both polishing and sanding applications.
- Flexible battery system: works with all Milwaukee® M12™ batteries.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Large capacity of 76 mm polishing sponge and 50 mm sanding pad size for fast job completion.
- Long run time allows frequent task completion with one battery charge.
- Compact design with only 130 mm allows access to hard areas.
- Spindle lock allows fast, tool free accessory change.

	M12 BPS-0
Battery pack capacity (Ah)	-
Battery type	Li-ion
Charger supplied	-
Disc diameter (mm)	76
No load speed (rpm)	2500 / 7500
No load speed gear 1 (rpm)	0 - 2800
No load speed gear 2 (rpm)	0 - 8300
No. of batteries supplied	0
Sound power level (dB(A))	79.2
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	68.24
Sound pressure level uncertainty (dB(A))	3
Spindle size	M9 x 0.75
Standard equipment	Polishing pad, sanding pad, polishing sponge white, polishing sponge yellow, lambswool, side handle
Supplied in	-
Vibration polishing (m/s <sup>2</sup> )	2.95
Vibration polishing uncertainty (m/s <sup>2</sup> )	1.83
Vibration sanding (m/s <sup>2</sup> )	2.3
Vibration sanding uncertainty (m/s <sup>2</sup> )	1.5
Voltage (V)	12
Weight with battery pack (kg)	-