

M12 BS-402C | M12™ sub compact bandsaw



- Compact light weight design for cutting with one hand overhead in existing installations and in tight spaces.
- Supplied with a 18 Tpi blade.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Cuts a multitude of materials: steel, stainless steel, copper, plastic, aluminium.
- Cold cutting - spark and burr free.
- Clean cut - balanced handle design combined with 8-large ball bearing blade supports provide best in class cut quality.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.

	M12 BS-402C
Battery pack capacity (Ah)	4.0
Battery type	Li-ion
Blade length (mm)	687.57
Charger supplied	80 min
Max. cutting capacity (mm)	41 x 41
No load speed (rpm)	0 - 85
No. of batteries supplied	2
Sound power level (dB(A))	85
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	74
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Blade 18 Tpi
Supplied in	Kitbox
Vibration level (m/s ²)	<2.5
Vibration uncertainty (m/s ²)	1.5
Voltage (V)	12
Weight with battery pack (kg)	3.2