

M12 BPRT-0 | M12™ sub compact rivet tool



- Up to 325 x 4.8 mm stainless steel rivets on a single charge with a 2.0 Ah battery pack.
- Suitable for all aluminium, steel, stainless steel and copper rivets up to 4.8 mm.
- Rivets in one stroke with a 20.32 mm stroke length.
- Retention nose pieces hold rivets in any orientation.
- Tool-free access to easily clean jaws. On-board nose piece storage and removal tool for user convenience.
- On board fuel gauge and LED light for added user convenience and illumination in low lit working conditions.
- Ergonomic design with 273 mm H x 66.8 mm W x 165 mm in length without mandrel collector.

	M12 BPRT-0
Battery pack capacity (Ah)	-
Battery type	-
Charger supplied	-
Dimensions (mm)	273 x 66 x 8 x 230
Max. pulling force (N)	9000
Max. rivets popped with M12 B2 battery (mm)	325 x 4.8
No. of batteries supplied	0
Rivet diameter range (mm)	2.4 - 4.8
Sound power level measured (dB(A))	64.1
Sound power level measured uncertainty (dB(A))	3
Sound pressure level (dB(A))	53.1
Sound pressure level uncertainty (dB(A))	3
Stroke length (mm)	20.32
Supplied in	-
Tips supplied (mm)	2.4, 3.2, 4.0, 4.8
Vibration level (m/s ²)	0.1
Vibration uncertainty (m/s ²)	1.5
Voltage (DC) (V)	12
Voltage (V)	12
Weight with battery pack (kg)	-