


## Preflex prewired conduit with ML installation wire

Preflex prewired conduit with H07V-U (ML) 3x2,5mm<sup>2</sup>  
0428703



### Product characteristics

|            |                |
|------------|----------------|
| Weight     | 15,5 kg        |
| Dimensions |                |
| Packaging  | coil           |
| Length (M) | 100m           |
| Category   | Energy & Light |

### Preflex® conduit characteristics

|                       |  |
|-----------------------|--|
| Material              | Halogen free Polypropylene   |
| Colour                | Grey   |
| Outer diameter        | 20mm   |
| Inner diameter        | 14,1mm   |
| Classification        | ICTA3422   |
| Pressure resistance   | 750N/23°C  |
| Impact resistance     | 6J/-5°C  |
| Bearer                | 2000V/ 50-60Hz 15min   |
| Insulation resistance | min. 100 Mohm/80cm   |
| Installation temp.    | -5° - +90°C  |
| Norms & Certificats   | EN 61386-1 EN61386-22 EN 60423 EN 61034 EN 60754-1 EN 60754-2<br>KEMAKEUR - CEBEC - AENOR - NF - VDE - CE - RoHS |

### Cable characteristics

|                            |                            |
|----------------------------|----------------------------|
| <b>Installation wire</b>   | <b>H07V-U ML Eca</b>       |
| Conductor                  | Solid plain copper class 1 |
| Insulation                 | PVC                        |
| Min. install. temp.        | +5°C                       |
| Max. conductor temp.       | +70°C                      |
| Operating temp.            | -40/+50°C                  |
| Euro fire class EN 13501-6 | Eca                        |
| Nominal Voltage            | 450/750V                   |
| Test Voltage               | 2,5 kV                     |
| Core colors                | G/Y, blue, brown           |
| Norms & Certificats        | EN 50575<br>NEN-EN 50525   |