

## Preflex prewired conduit with ML installation wire

Preflex prewired conduit with H07V-U (ML) 5x1,5mm<sup>2</sup>  
0428707

### Product characteristics

Weight	15,8 kg
Packaging	coil
Length (M)	100m
Category	Light



### Preflex® conduit characteristics

Material	Halogen free Polypropylene
Colour	Grey
Outer diameter	20mm
Inner diameter	14,1mm
Classification	ICTA3422
Pressure resistance	750N/23°C
Impact resistance	6J/-5°C
Bearer	2000V/ 50-60Hz 15min
Insulation resistance	min. 100 Mohm/80cm
Installation temp.	-5° - +90°C
Norms & Certificats	EN 61386-1 EN61386-22 EN 60423 EN 61034 EN 60754-1 EN 60754-2 KEMAKEUR - CEBC - AENOR - NF - VDE - CE - RoHS

### Cable characteristics

<b>Installation wire</b>	<b>H07V-U ML Eca</b>
Conductor	Solid plain copper class 1
Insulation	PVC
Min. install. temp.	+5°C
Max. conductor temp.	+70°C
Operating temp.	-40/+50°C
Euro fire class EN 13501-6	Eca
Nominal Voltage	450/750V
Test Voltage	2,5 kV
Core colors	G/Y, blue, brown, black, grey
Norms & Certificats	EN 50575 NEN-EN 50525