

## 0390 - Sealing Strip, various dimensions

<b>Description</b>	This extruded sealing strip consists of a synthetic rubber butyl adhesive, supplied on a liner.
<b>Product properties</b>	It is highly conformable with good adhesion to a wide variety of substrates, with good resistance to ageing, humidity, water, chemicals and UV-light. It remains flexible through its service life and is easy and accurate to use.  It is supplied in a wide range of dimensions and formats.
<b>Applications</b>	It is used for various sealing and joining applications, such as joining plastic sheeting such as DPCs and DPMS, for sealing a variety of joints in roofing and cladding systems and for sealing panels in slurry storage tanks and silos. It is used as a gap filling sealant in body-in-white applications on vehicles and for sealing of light clusters.
<b>Storage and ageing</b>	2 year shelf life whilst stored in original packaging and ambient room temperature. Keep out of direct sunlight.
<b>Applying tips</b>	All substrates should be clean and contamination free, a solvent such as Isopropyl-Alcohol is recommended for cleaning purposes, and the tape should be applied with pressure.
<b>Additional technical properties</b>	Force to compress by 20%: 5 N/cm <sup>2</sup>

### TECHNICAL DATA

<b>Carrier</b>	None	
<b>Adhesive</b>	Rubber butyl	
<b>Colour</b>	Black	
<b>Liner</b>	Paper silicone coated	
<b>Weather resistant</b>	Yes	
<b>UV resistant</b>	Yes	
<b>Ageing resistant</b>	Yes	
<b>Density</b>	1100 kg/m <sup>3</sup>	68,7 Lb/ft <sup>3</sup>
<b>Adhesion on stainless steel</b>	45 N/25mm	10,3 Lbs/inch
<b>Dynamic shear</b>	94 N/625mm <sup>2</sup>	21,4 Lb/inch <sup>2</sup>
<b>Service temperature</b>	Between -40 and 90 °C	Between -40 and 194 °F
<b>Application temperature</b>	Minimum 4 °C	Minimum 39,2 °F
<b>Water vapour transmission rate</b>	0,13 g/m <sup>2</sup> /24h	0,000343 lb/yard <sup>2</sup> /24h

Disclaimer: Values shown in this document are averages only. For legal reasons, we emphasize that the information on this data is available "as is" and that Stokvis Tapes, an ITW company, gives no guarantees with respect to the accuracy and completeness nor with respect to interpretations made on the basis of this information.

See our applicable delivery conditions. Each user should conduct his own tests to determine the suitability of the product for his intended use and shall assume all risks and liability in connection therewith. Stokvis Tapes cannot be held liable for any damages resulting from the unsuitability of the product. Many factors beyond the control of Stokvis Tapes may affect the use and performance of the product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluates the Stokvis Tapes product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

The information is available to the user for viewing, copying and distributing, provided that Stokvis Tapes, an ITW company, is always quoted as the source. The information is intended solely for informational and non-commercial use.

Intellectual property: Stokvis Tapes, an ITW company, reserves all rights regarding this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly forbidden.

**Stokvis Tapes Finland**  
 Tehtaantie 1  
 03100 Nummela  
 tel +358 207 199 940  
 fax +358 207 199 941  
 www.stokvistapes.fi  
 info@stokvistapes.fi

