



## 300 - 310 Wp

## AXIworldprotect MT BLK

60 cell glass/glass monocrystalline  
High performance solar module


The advantages:

- 15** Years 15 years manufacturer's warranty
- PID free** PID-free through glass/glass-technology
- + Wp** Guaranteed positive power tolerance from 0-5 Wp by individual measurement
- 5.400 Pa** Maximum 5400 Pa snow load
- 100%** 100% electroluminescence inspection
- IP 67** High quality junction box and connector systems



Exclusive linear AXITEC high performance guarantee!

- 15 years manufacturer's guarantee on 90% of the nominal performance
- 30 years manufacturer's guarantee on 82,5% of the nominal performance





## AXIworldprotect MT BLK 300 - 310 Wp

**Electrical data** (at standard conditions (STC) irradiance 1000 watt/m<sup>2</sup>, spectrum AM 1,5 at a cell temperature of 25°C)

Type	Nominal output P <sub>mpp</sub>	Nominal voltage U <sub>mpp</sub>	Nominal current I <sub>mpp</sub>	Short circuit current I <sub>sc</sub>	Open circuit voltage U <sub>oc</sub>	Module conversion efficiency
AC-300MG/60S	300 Wp	32,37 V	9,27 A	9,74 A	39,72 V	18,07 %
AC-305MG/60S	305 Wp	32,63 V	9,35 A	9,79 A	39,82 V	18,37 %
AC-310MG/60S	310 Wp	32,95 V	9,41 A	9,83 A	39,91 V	18,67 %

### Design


Frontside	2 x 2,5 mm hardened, low-reflection white glass
Cells	60 monocrystalline high efficiency cells
Backside	Composite film (transparent)
Frame	35 mm black aluminium frame

### Mechanical data

L x W x H	1664 x 998 x 35 mm
Weight	24,0 kg with frame

### Power connection

Socket	Protection Class IP67
Wire	approx. 1,1 m, 4 mm <sup>2</sup>
Plug-in system	Plug/socket IP67, MC4



All dimensions in mm

### Limit values

System voltage	1000 VDC
NOCT (nominal operating cell temperature)*	45°C +/-2K
Max. load-carrying capacity	5400 N/m <sup>2</sup>
Reverse current feed IR	20,0 A
Permissible operating temperature	-40°C to 85°C / -40F to 185F

(No external voltages greater than U<sub>oc</sub> may be applied to the module)

\* NOCT, irradiance 800 W/m<sup>2</sup>; AM 1,5; wind speed 1 m/s; Temperature 20°C

### Temperature coefficients

Voltage U <sub>oc</sub>	-0,29 %/K
Current I <sub>sc</sub>	0,04 %/K
Output P <sub>mpp</sub>	-0,39 %/K

### Low-light performance

 (Example for AC-300MG/60S)

I-U characteristic curve	Current I <sub>pp</sub>	Voltage U <sub>pp</sub>
200 W/m <sup>2</sup>	2,15 A	30,17 V
400 W/m <sup>2</sup>	3,71 A	31,20 V
600 W/m <sup>2</sup>	6,05 A	31,81 V
800 W/m <sup>2</sup>	7,57 A	32,10 V
1000 W/m <sup>2</sup>	9,27 A	32,37 V