


OSRA 32 / M32(M)*M16(F)

Ex d reduction adaptor, brass nickel-plated, M32-M16



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material	Brass nickel-plated
Temp. range min	-60 °C
Temp. range max	110 °C
Protection class	IP66 / IP67
Type of protection	Ex eb, Ex tb, Ex db
Ex-Certificate	IECEX, ATEX
Thread type outer	M
Ø outer thread	32
Lead outer	1,5
Length screw-in thread L	15 mm
Thread type inner	M
Ø inner thread	16
Lead inner	1,5
Key width SW	38 mm
Collar diameter (E)	41 mm
Total length TL	20 mm
Order no. nickel-plated	50065653
Type	OSRA 32 / M32(M)*M16(F)
Packing unit	1
ETIM-Classification	EC000938

08.07.2020

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com