

Preflex SAFE prewired conduit with coaxial cable

Preflex prewired conduit with Class A coaxial cable
[0262472](#)

Product characteristics

Weight	11kg
Dimensions	61cm x 61cm x 19cm
Packaging	coil
EAN	6410002624724
Lenght (M)	100m
Category	TV



Preflex® conduit characteristics

Material	Halogen free Polypropylene
Colour	Grey
Outer diameter	20mm
Inner diameter	14,1mm
Classification	ICTA3422
Pressure resistance	750N/23°C
Impact resistance	6J/-5°C
Bearer	2000V/ 50-60Hz 15min
Insulation resistance	min. 100 Mohm/80cm
Installation temp.	-5° - +90°C
Norms & Certificats	EN 61386-1 EN61386-22 EN 60423 EN 61034 EN 60754-1 EN 60754-2 KEMAKEUR - CEBEC - AENOR - NF - VDE - CE - RoHS

Cable characteristics

SAT5 Class A coaxial cable LSZH

Core	Bare copper 0,81mm
Nominal diameter	5,7mm
Braiding	Alu 16x5x0,12mm - coverage 65%
Insulation	LSOH white
Impedance	75 Ohm
Nominal capacity	54pF/m
Screening attenuation	≥85 dB (Class A+ 30-1000Mhz)
Propagation speed	82%
Insulation resistance	≥5000 Mohm/Km
CPR Class	Cca s1a1